

View Online at <https://aerobasegroup.com/nsn/4820-00-545-0788>

Pipe Size Accommodated:

0.250 inches all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Piston

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.0 gallons per minute

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Features Provided:

Pressure tight outlet side

Thready Qty Per Inch (tpi):

18 all ends

Adjustable Pressure Range:

+150.0/+3000.0 pounds per square inch

Maximum Operating Pressure:

6000.0 pounds per square inch single response

Thread Size:

0.250 inches all ends

Opening Pressure Setting:

1500.0 pounds per square inch

Special Features:

W/two mtg holes 0.344 in. Dia. Through body and pressure screw adjustment w/buna-n seals

Material:

Aluminum alloy

Media For Which Designed:

Oil, hydraulic single response

Style Designator:

Angle

Thread Series Designator:

Nptf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0