NSN 4820-00-545-0788

Safety Relief Valve - Page 1 of 2

Nptf all ends



View Online at https://aerobasegroup.com/nsn/4820-00-545-0788

Pipe Size Accommodated:
0.250 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Piston
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
3.0 gallons per minute
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 all ends
Adjustable Pressure Range:
+150.0/+3000.0 pounds per square inch
Maximum Operating Pressure:
6000.0 pounds per square inch single response
Thread Size:
0.250 inches all ends
Opening Pressure Setting:
1500.0 pounds per square inch
Special Features:
W/two mtg holes 0.344 in. Dia. Through body and pressure screw adjustment w/buna-n seals
Material:
Aluminum alloy
Media For Which Designed:
Oil, hydraulic single response
Style Designator:
Angle
Thread Series Designator:

NSN 4820-00-545-0788

Safety Relief Valve - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0