## NSN 4820-00-549-4733

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-549-4733

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
-40.0 degrees fahrenheit 1st response250.0 degrees fahrenheit 2nd response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
200.0 pounds per square inch 1st response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
10.0 pounds per square inch
Special Features:
Pop-off type
Material:
Copper alloy
Media For Which Designed:
Hydrogen 5th response
Style Designator:
Straight through note: to be used for valve bodies of one section only.
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 4820-00-549-4733

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0