

View Online at <https://aerobasegroup.com/nsn/4820-00-551-0757>

Body Material:

Any acceptable

Outside Surface Treatment:

Any acceptable

Body Style:

Angle

Stem Material:

Any acceptable

Furnished Items:

Automatic relief valve

Media For Which Designed:

Acetylene

First End Connection Type:

Threaded external tube

First End Style Designator:

Flared

First End Outside Diameter Tube Accommodated:

0.375 inches

First End Thread Size And Series/type Designator:

9/16-18 unf

First End Thread Class:

3a

First End Thread Direction:

Left-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded internal gas cylinder

Second End Style Designator:

Swivel nut, inverted flare

Second End Thread Size And Series/type Designator:

0.620-20 ngo

Second End Thread Direction:

Right-hand

Seat Material:

Any acceptable

First End Seat Angle In Deg:

30.0

Flow Control Device:

Disk, flat, top and bottom guided

Flow Control Device Material:

Any acceptable

End Connection Quantity:

2

Second End Thread Pitch Diameters:

Any acceptable

Renewable Seat Ring Type:

Threaded

Outlet Pressure Range:

+6.5 to 7.5 pounds per square inch

Regulation Type:

Manual single stage

Manual Control Method:

Tee handle

Valve Stem Design:

Single seat

Valve Loading Method:

Spring

Remote Actuation Method:

Diaphragm

Maximum Inlet Pressure Rating:

350.0 pounds per square inch

Outlet Pressure Accuracy Rating:

3.500 pounds per square inch

Filter:

Included

Tempurature Rating:

Between -40.0 degrees fahrenheit and 165.0 degrees fahrenheit

Specification Or Standard:

1 type and a+1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100