

View Online at <https://aerobasegroup.com/nsn/4820-00-551-1094>

Body Material:

Any acceptable

Body Style:

Straight thru

Furnished Items:

Bonnet and dial and indicator

Media For Which Designed:

Acetylene

First End Connection Type:

Threaded external tube

First End Style Designator:

Compression

First End Outside Diameter Tube Accommodated:

0.250 inches

First End Thread Size And Series/type Designator:

9/16-18 unf

First End Thread Class:

2a

First End Thread Direction:

Left-hand

Second End Relationship With First End:

Not identical

Second End Connection Type:

Threaded external tube

Second End Style Designator:

Flared

Second End Outside Diameter Tube Accommodated:

0.625 inches

Second End Thread Size And Series/type Designator:

0.880-14 ngo

Second End Thread Class:

2a

Second End Thread Direction:

Left-hand

First End Seat Angle In Deg:

Any acceptable

Second End Seat Angle In Deg:

37.0

First End Seat Radius:

0.062 inches

Flow Control Device:

Diaphragm

Flow Control Device Material:

Steel, corrosion resisting

End Connection Quantity:

2

Regulation Type:

Manual single stage

Manual Control Method:

Knob

Valve Loading Method:

Spring

Maximum Inlet Pressure Rating:

400.0 pounds per square inch

Outlet Pressure Accuracy Rating:

Not rated

Filter:

Included

Unable To Decode:

Unable to decode and unable to decode

Temperature Rating:

Between -40.0 degrees fahrenheit and 165.0 degrees fahrenheit

Specification Or Standard:

1 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A21100