NSN 4820-00-552-3508

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-552-3508

Thread Direction: Right-hand 1st end **Flow Control Device: Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 225.0 degrees fahrenheit single response **Connection Style:** Plain, optional en (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal pipe 1st end **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 3100.0 pounds per square inch single response **Thread Size:** 0.250 inches 2nd end **Opening Pressure Setting:** 200.0 pounds per square inch **Special Features:** The end connection identified above as the second end is the valve inlet Material: Steel comp 416 flow control device **Material Specification:** Qq-b-626, alloy 360 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon 3rd response **Style Designator:** Angle **Thread Series Designator:** Anpt 2nd end Shelf Life: N/a **Unit Of Measure:**

NSN 4820-00-552-3508

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0