NSN 4820-00-554-7211



Restrictor Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-554-7211 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Flareless all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends Seat Angle: 12.0 degrees all ends Material: Steel comp 303 flow control device **Material Specification:** Qq-s-764, type 303 federal specification single material response flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-554-7211

Restrictor Check Valve - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.