NSN 4820-00-554-8528



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-554-8528 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Plain (tube) 2nd end **Valve Operation Method:** Automatic **Connection Type:** Unthreaded external tube 2nd end **Features Provided:** Valve stem lock shield and bonnet packing Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 3630.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end **Opening Pressure Setting:** 1700.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 2nd end Material: Stainless steel stem Media For Which Designed:

Air single response

Style Designator:

Angle

Thread Series Designator:

Unf 1st end

NSN 4820-00-554-8528

Safety Relief Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0