NSN 4820-00-555-0000



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-555-0000 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Bonnet Type:** Packing retaining **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 2.5 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 20 all ends **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Opening Pressure Setting:** 1500.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Stainless steel seat **Material Specification:** Qq-a-225/6, alloy 2024 federal specification single material response body Media For Which Designed: Hydraulic fluid, mineral base single response **Surface Treatment:** Anodize



NSN 4820-00-555-0000

Safety Relief Valve - Page 2 of 2



Thread	Series	Designator:

Unjf all ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0