NSN 4820-00-568-0156



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-568-0156 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 16.0 gallons per minute **Connection Style:** Gasket sea (boss) 1st end **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 12 1st end **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 1.062 inches 1st end **Opening Pressure Setting:** 1800.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.750 inches 1st end **Special Features:** Free reverse flow Material: Stainless steel seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Thread Series Designator:**

Unf 1st end Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 4820-00-568-0156

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0