## NSN 4820-00-580-2587

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:



View Online at https://aerobasegroup.com/nsn/4820-00-580-2587

0.750 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
559.0 cubic feet per minute
Maximum Operating Temp:
250.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
<b>Maximum Operating Pressure:</b>
300.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Opening Pressure Setting:
125.0 pounds per square inch
Material:
Steel stem
Media For Which Designed:
Air single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

## NSN 4820-00-580-2587

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0