NSN 4820-00-580-6035

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-580-6035 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Swivel nut, flareless (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Mounting Position:** Horizontal **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.875 inches all ends Seat Angle: 45.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.625 inches all ends **Special Features:** Over-all dim., 4.125 in. Lg, 1.125 in. Across flats Material: Stainless steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life:

N/a Unit Of Measure: --

NSN 4820-00-580-6035

Restrictor Check Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A530b0