NSN 4820-00-580-6615



Poppet Drain Cock - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-580-6615 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Maximum Operating Temp:** 160.0 degrees fahrenheit single response **End Application:** E-2c hawkeye, c-2a (reprocured), c-130 hercules, sof (ac-130h, mc-130h, ec-130e, hc-130) aircraft. **Connection Style:** Plain (tube) 1st end **Valve Operation Method:** Manual **Connection Type:** Threaded external tube 1st end Thready Qty Per Inch (tpi): 20 1st end **Maximum Operating Pressure:** 60.0 pounds per square inch 1st response **Thread Size:** 0.437 inches 1st end Seat Angle: 37.0 degrees 1st end **Criticality Code Justification:** Feat **Outside Diameter Tube Accommodated:** 0.250 inches 1st end **Special Features:** Weapon system essential Material: Copper alloy body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Cadmium **Style Designator:** Straight thru **Thread Series Designator:** Unf 1st end

N/a

Shelf Life:

NSN 4820-00-580-6615

Poppet Drain Cock - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A530c0