NSN 4820-00-585-7567

Globe Valve - Page 1 of 2

Thread Direction:



View Online at https://aerobasegroup.com/nsn/4820-00-585-7567

| Right-hand 2nd end |
|--|
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Threaded |
| Bolt Hole Quantity: |
| 6 1st end |
| Connection Style: |
| Plain (hose) 2nd end |
| Valve Operation Method: |
| Manual |
| Flange Shape: |
| Round with holes 1st end |
| Connection Type: |
| Threaded external hose 2nd end |
| Thready Qty Per Inch (tpi): |
| 11-1/2 2nd end |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Thread Size: |
| 1.500 inches 2nd end |
| Outside Diameter: |
| 5.062 inches 1st end |
| Thickness: |
| 0.812 inches 1st end |
| Bolt Hole Diameter: |
| 0.562 inches 1st end |
| Bolt Circle Diameter: |
| 3.938 inches 1st end |
| Flange Face Design: |
| Plain 1st end |
| Outside Diameter Hose Accommodated: |
| 1.500 inches 2nd end |
| Material: |
| Nickel alloy stem |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Npsh 2nd end |

NSN 4820-00-585-7567

Globe Valve - Page 2 of 2



| She | lf | I if | ρ. |
|-----|-----|------|----|
| ~ | ••• | | • |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0