## NSN 4820-00-585-7859

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

**Bonnet Attachment Method:** 

0.250 inches 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-00-585-7859

Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
300.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
Maximum Operating Pressure:
225.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
60.0 pounds per square inch
Special Features:
Lox cleaned per mil-m-9950
Material:
Copper alloy
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Reference Number Differentiating Characteristics:
As differentiated by relief pressure setting and size of valve
Shelf Life:
N/a

## NSN 4820-00-585-7859

Safety Relief Valve - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0