NSN 4820-00-585-7859

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-585-7859

Pipe Size Accommodated: 0.250 inches 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Poppet **Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring Maximum Operating Temp: 300.0 degrees fahrenheit single response **Connection Style:** Plain (pipe) 1st end Valve Operation Method: Automatic or manual **Connection Type:** Threaded external pipe 1st end **Features Provided:** Valve stem lock shield Maximum Operating Pressure: 225.0 pounds per square inch single response **Thread Size:** 0.250 inches 1st end **Opening Pressure Setting:** 60.0 pounds per square inch **Special Features:** Lox cleaned per mil-m-9950 Material: Copper alloy Media For Which Designed: Gas, natural 2nd response Style Designator: Angle **Thread Series Designator:** Npt 1st end **Reference Number Differentiating Characteristics:** As differentiated by relief pressure setting and size of valve Shelf Life: N/a

NSN 4820-00-585-7859

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

