NSN 4820-00-585-8566

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-585-8566

Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
504.0 pounds per hour
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Features Provided:
Valve stem lock shield
Thready Qty Per Inch (tpi):
18 1st end
Maximum Operating Pressure:
350.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
325.0 pounds per square inch
Material:
Steel seat
Media For Which Designed:
Steam single response
Style Designator:
Angle
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a

NSN 4820-00-585-8566

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0