NSN 4820-00-588-0669

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-588-0669

| Thread Direction: |
|--|
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 45.0 cubic feet per minute |
| Maximum Operating Temp: |
| 300.0 degrees fahrenheit single response |
| End Application: |
| Grumman aerospace a10 aircraft |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic or manual |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch single response |
| Thread Size: |
| 0.375 inches 1st end |
| Opening Pressure Setting: |
| 75.0 pounds per square inch |
| Material: |
| Copper alloy |
| Media For Which Designed: |
| Gas, natural 2nd response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |

NSN 4820-00-588-0669

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

