NSN 4820-00-593-2233

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-593-2233

Pipe Size Accommodated:

0.750 inches all ends

Thread Direction:

Right-hand all ends

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Integral

Disk Loading Method:

Spring

Maximum Operating Temp:

225.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Automatic

Connection Type:

Threaded internal pipe all ends

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

14 all ends

Adjustable Pressure Range:

+800.0/+1500.0 pounds per square inch

Maximum Operating Pressure:

3100.0 pounds per square inch single response

Thread Size:

0.750 inches all ends

Opening Pressure Setting:

1000.0 pounds per square inch

Material:

Stainless steel stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Angle

Thread Series Designator:

Npt all ends

Shelf Life:

N/a

NSN 4820-00-593-2233

Safety Relief Valve - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A046b0

