## NSN 4820-00-593-2233

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-593-2233

Pipe Size Accommodated:
0.750 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
225.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Valve stem lock shield and bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
14 all ends
Adjustable Pressure Range:
+800.0/+1500.0 pounds per square inch
Maximum Operating Pressure:
3100.0 pounds per square inch single response
Thread Size:
0.750 inches all ends
Opening Pressure Setting:
1000.0 pounds per square inch
Material:
Stainless steel stem
Media For Which Designed:
Water-oil-gas single response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:

N/a

## NSN 4820-00-593-2233

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0