## NSN 4820-00-595-0496

Stop-check Valve - Page 1 of 2

**Flow Control Device:** 

**Bonnet Type:** 

Disk

View Online at https://aerobasegroup.com/nsn/4820-00-595-0496



Inside screw **Bonnet Attachment Method:** Union **Renewable Seat Ring Type:** Threaded **Bolt Hole Quantity:** 4 1st end Maximum Operating Temp: 425.0 degrees fahrenheit single response Valve Operation Method: Manual Flange Shape: Round with holes 1st end **Connection Type:** Flange 1st end **Mounting Position:** Horizontal **Features Provided:** Bonnet packing Valve Size: 1.000 inches Maximum Operating Pressure: 100.0 pounds per square inch single response **Outside Diameter:** 4.250 inches 1st end Face To Face Distance: 5.750 inches Thickness: 0.438 inches 1st end **Bolt Hole Diameter:** 0.562 inches 1st end **Bolt Circle Diameter:** 3.125 inches 1st end Flange Face Design: Plain 1st end **Special Features:** Valve size 1.000 in. Media For Which Designed: Water-oil-gas single response

## NSN 4820-00-595-0496

Stop-check Valve - Page 2 of 2



Style Designator:

Straight through flanged ends

## **Test Data Document:**

80064-5000s4824-1385541 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

## Unit Of Measure:

---

Demilitarization:

No

Fiig:

A530b0