NSN 4820-00-595-2931

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-595-2931

Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 all ends
Maximum Operating Temp:
250.0 degrees fahrenheit 2nd response
Valve Operation Method:
Automatic
Flange Shape:
Round with holes all ends
Connection Type:
Flange all ends
Valve Size:
1.500 inches
Maximum Operating Pressure:
275.0 pounds per square inch 1st response
Opening Pressure Setting:
19.0 pounds per square inch
Outside Diameter:
6.000 inches 1st end
Thickness:
0.562 inches all ends
First Connection Face To Centerline Distance:
4.750 inches
Bolt Hole Diameter:
0.750 inches 1st end
Second Connection Face To Centerline Distance:
4.875 inches
Bolt Circle Diameter:
4.750 inches 1st end
Flange Face Design:
Raised straight all ends
Raised Face Height:
0.688 inches 2nd end
Raised Face Diameter:
3.625 inches 1st end

NSN 4820-00-595-2931

Safety Relief Valve - Page 2 of 2



M	lat	Or	וכו	

Steel uns j03002 body

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0