Screw Stem Shutoff Cock - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-595-3192

-	Size Accommodated:
) inches 1st end
	ad Class:
2a 2r	nd end
Thre	ad Direction:
Right	t-hand 1st end
Flow	Control Device:
Disk	
End	Application:
Grum	nmin aerospace a10 aircraft
Conr	nection Style:
Plain	(pipe) 1st end
Valve	e Operation Method:
Manu	Jal
Conr	nection Type:
Threa	aded external tube 2nd end
Thre	ady Qty Per Inch (tpi):
24 2r	nd end
Maxi	mum Operating Pressure:
400.0) pounds per square inch 2nd response
Thre	ad Size:
0.500) inches 2nd end
Seat	Radius:
0.062	2 inches 2nd end
Outs	ide Diameter Tube Accommodated:
0.313	3 inches 2nd end
Mate	rial:
Copp	per alloy
Medi	a For Which Designed:
Nitro	gen, gaseous 2nd response
Style	Designator:
Strai	ght thru
Thre	ad Series Designator:
Uns :	2nd end
Furn	ished Items And Quantity:
1 feri	rule
Shel	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	

NSN 4820-00-595-3192

Screw Stem Shutoff Cock - Page 2 of 2

Fiig: A530c0

