NSN 4820-00-599-9368



Fluid Pressure Regulating Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-599-9368 **Body Material: Brass Outside Surface Treatment:** Any acceptable **Body Style:** Angle **Furnished Items:** Adapter and automatic relief valve and inlet pressure gage and outlet pressure gage Media For Which Designed: Oxygen, gaseous **First End Connection Type:** Threaded internal pipe First End Style Designator: Optional end First End Thread Size And Series/type Designator: 1/4-18 npt **First End Thread Direction:** Right-hand Second End Relationship With First End: Not identical **Second End Connection Type:** Threaded internal gas cylinder **Second End Style Designator:** Swivel nut, gas Second End Thread Size And Series/type Designator: 0.908-14 ngo **Second End Thread Direction:** Right-hand **Seat Material: Brass** Flow Control Device: Disk, flat, top and bottom guided Flow Control Device Material: Steel, corrosion resisting **End Connection Quantity: Second End Thread Pitch Diameters:**

Any acceptable

Renewable Seat Ring Type:

Threaded

Outlet Pressure Range:

+0.0 to 40.0 pounds per square inch

NSN 4820-00-599-9368

Fluid Pressure Regulating Valve - Page 2 of 2



Regulation Type:
Automatic double stage
Valve Stem Design:
Double seat
Valve Loading Method:
Spring
Remote Actuation Method:
Diaphragm
Maximum Inlet Pressure Rating:
2600.0 pounds per square inch
Outlet Pressure Accuracy Rating:
Not rated
Filter:
Included
Unable To Decode:
Unable to decode and unable to decode
Tempurature Rating:
120.0 degrees fahrenheit
Special Features:
9.5 cfm maximum flow capacity at maximum rated inlet and outlet pressures, adapter for outlet connection straight pipe to hose
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A21100