## NSN 4820-00-601-3790

Lift-check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-601-3790
Pipe Size Accommodated:
0.250 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket seal (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Mounting Facility:
Threaded fastener
Mounting Position:
Horizontal
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
45.0 degrees 1st end
Material:
Stainless steel stem
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Surface Treatment:
Anodize or passivate
Style Designator:
Straight thru
Test Data Document:
76301-20-91524 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Unjf 1st end

**Thread Series Designator:** 

## NSN 4820-00-601-3790

Lift-check Valve - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0