NSN 4820-00-604-4656

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-604-4656 **Thread Class:** 3a 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Renewable Seat Ring Type:** Pressed-in **Maximum Operating Temp:** 250.0 degrees fahrenheit 2nd response **Connection Style:** Plain (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube 1st end **Maximum Operating Pressure:** 200.0 pounds per square inch single response **Thread Size:** 0.438 inches 1st end **Opening Pressure Setting:** 50.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Material: Aluminum alloy seat Media For Which Designed: Air 1st responsealcohol, ethyl 2nd responseammonia, gaseous 3rd responsefuel/oil, hydrocarbon 4th responsehelium 5th response **Style Designator:** Straight through w/baffle **Thread Series Designator:** Unif 1st end **Furnished Items And Quantity:** 1 deflector cap Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 4820-00-604-4656

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0