NSN 4820-00-606-1622

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-606-1622

| Pipe Size Accommodated: |
|---|
| 0.500 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Piston |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain, optional en (pipe) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal pipe 2nd end |
| Features Provided: |
| Pressure tight outlet side |
| Thready Qty Per Inch (tpi): |
| 27 2nd end |
| Adjustable Pressure Range: |
| +3000.0/+3500.0 pounds per square inch |
| Maximum Operating Pressure: |
| 3500.0 pounds per square inch single response |
| Thread Size: |
| 0.500 inches 1st end |
| Opening Pressure Setting: |
| 3500.0 pounds per square inch |
| Material: |
| Copper alloy body |
| Media For Which Designed: |
| Air single response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |