

View Online at <https://aerobasegroup.com/nsn/4820-00-608-0971>

Flow Control Device:

Disk or stem

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Bolt Hole Quantity:

8 1st end

Maximum Operating Temp:

650.0 degrees fahrenheit single response

Valve Operation Method:

Manual

Flange Shape:

Round with holes 1st end

Connection Type:

Flange 1st end

Mounting Facility:

Bracket

Valve Size:

3.000 inches

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter:

6.625 inches 1st end

Thickness:

0.562 inches 1st end

First Connection Face To Centerline Distance:

5.000 inches

Bolt Hole Diameter:

0.625 inches 1st end

Second Connection Face To Centerline Distance:

5.000 inches

Bolt Circle Diameter:

5.500 inches 1st end

Flange Face Design:

Raised straight 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

4.750 inches 1st end

Material:

Steel uns j03008 seat

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0