NSN 4820-00-618-3016

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-618-3016

Pipe Size Accommodated:

| 2.500 inches 2nd end |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 406.0 degrees fahrenheit 1st response |
| Connection Style: |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method: |
| Automatic or manual |
| Connection Type: |
| Threaded internal pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Adjustable Pressure Range: |
| +0.0/+300.0 pounds per square inch |
| Maximum Operating Pressure: |
| 300.0 pounds per square inch 2nd response |
| Thread Size: |
| 2.500 inches 2nd end |
| Material: |
| Copper alloy |
| Media For Which Designed: |
| Gas, inert 3rd response |
| Style Designator: |
| Angle |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 4820-00-618-3016

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0