NSN 4820-00-618-4988

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

0.750 inches 1st end



View Online at https://aerobasegroup.com/nsn/4820-00-618-4988

Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
427.0 cubic feet per minute
Maximum Operating Temp:
400.0 degrees fahrenheit single response
Connection Style:
Plain (pipe) 1st end
Valve Operation Method:
Automatic or manual
Connection Type:
Threaded external pipe 1st end
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+0.0/+150.0 pounds per square inch
Maximum Operating Pressure:
150.0 pounds per square inch single response
Thread Size:
0.750 inches 1st end
Material:
Stainless steel stem
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-618-4988

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0