NSN 4820-00-618-4989

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-618-4989

| Pipe Size Accommodated: |
|---|
| 0.250 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Adjustable Pressure Range: |
| +10.0/+30.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Opening Pressure Setting: |
| 20.0 pounds per square inch |
| Special Features: |
| Pop-off type |
| Material: |
| Copper alloy |
| Media For Which Designed: |
| Hydrogen 5th response |
| Style Designator: |
| Straight through note: to be used for valve bodies of one section only. |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A046b0 |