NSN 4820-00-618-7001

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-618-7001

| View Online at https://aerobasegroup.com/nsn/4820-00 |
|--|
| Thread Class: |
| 3b all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 275.0 degrees fahrenheit single response |
| Connection Style: |
| Gasket seal (boss) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal boss all ends |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 16 all ends |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.750 inches all ends |
| Outside Diameter Tube Accommodated: |
| 0.500 inches all ends |
| Special Features: |
| Designed for hydraulic fluid |
| Material: |
| Aluminum alloy seat |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Unf all ends |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 4820-00-618-7001

Check Valve - Page 2 of 2

Fiig: A530b0

