NSN 4820-00-618-7035

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-618-7035

Thread Class: 3a 1st end Thread Direction: Right-hand 1st end Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Thread Direction: Right-hand 1st end Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Right-hand 1st end Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Flow Control Device: Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Poppet Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Disk Loading Method: Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Spring Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
Maximum Operating Temp: 250.0 degrees fahrenheit single response Connection Style:
250.0 degrees fahrenheit single response Connection Style:
Connection Style:
-
Plain (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external pipe 1st end
Adjustable Pressure Range:
+60.0/+140.0 pounds per square inch
Maximum Operating Pressure:
200.0 pounds per square inch single response
Thread Size:
0.250 inches 1st end
Opening Pressure Setting:
100.0 pounds per square inch
Special Features:
Pop-off type
Material:
Copper alloy
Media For Which Designed:
Hydrogen 5th response
Style Designator:
Straight through note: to be used for valve bodies of one section only.
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A046b0