NSN 4820-00-618-7743

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-618-7743 **Thread Direction:** Right-hand 1st end **Flow Control Device: Poppet Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 73.0 cubic feet per minute **Maximum Operating Temp:** 185.0 degrees fahrenheit single response **End Application:** Grummin aerospace a10 aircraft **Connection Style:** Plain (pipe) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded external pipe 1st end **Features Provided:** Pressure tight outlet side **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.250 inches 1st end **Opening Pressure Setting:** 1200.0 pounds per square inch Material: Steel comp 303 seat **Material Specification:** Fed standard 66 federal standard single material response seat Media For Which Designed: Air single response **Surface Treatment:** Anodize **Style Designator:**

Angle **Thread Series Designator:** Npt 1st end

NSN 4820-00-618-7743

Safety Relief Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0