NSN 4820-00-618-8653



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-618-8653 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Inside spring **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 8.0 gallons per minute Renewable Seat Ring Type: Threaded **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end Thready Qty Per Inch (tpi): 16 1st end **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 1500.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.500 inches 1st end Material: Stainless steel seat **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unf 1st end

Shelf Life: N/a

NSN 4820-00-618-8653

Safety Relief Valve - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0