

View Online at <https://aerobasegroup.com/nsn/4820-00-621-2458>

**Thread Class:**

3b

**End Connection Quantity:**

4

**Valve Discharge Flow Rate:**

20.0 gallons per minute

**End Application:**

Applicable t.O. 9h8-14-168-3 fig 5

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal boss

**Thready Qty Per Inch (tpi):**

12

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

1.063 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

160.0 degrees fahrenheit hydraulic fluid, petroleum base

**Spool Position Quantity:**

3

**Spool Quantity:**

2

**Special Features:**

8manufacturers suggested name is valve assembly, hydraulic crossover landing gear and flap control; operating fluid hydraulic fluid mil-h-5606; operating pressure 3000 psig; proof pressure 4500 psig; operating temp range -65 to +160 degrees feh; wt 5.25 lbs

**Thread Series Designator:**

Unj

**Furnished Items And Quantity:**

1 lever

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A506h0