

View Online at <https://aerobasegroup.com/nsn/4820-00-621-2458>

Thread Class:

3b

End Connection Quantity:

4

Valve Discharge Flow Rate:

20.0 gallons per minute

End Application:

Applicable t.O. 9h8-14-168-3 fig 5

Valve Operation Method:

Manual

Connection Type:

Threaded internal boss

Thready Qty Per Inch (tpi):

12

Maximum Operating Pressure And Media For Which Designed:

3000.0 pounds per square inch hydraulic fluid, petroleum base

Thread Size:

1.063 inches

Body Material:

Aluminum alloy

Maximum Operating Temperature And Media For Which Designed:

160.0 degrees fahrenheit hydraulic fluid, petroleum base

Spool Position Quantity:

3

Spool Quantity:

2

Special Features:

8manufacturers suggested name is valve assembly, hydraulic crossover landing gear and flap control; operating fluid hydraulic fluid mil-h-5606; operating pressure 3000 psig; proof pressure 4500 psig; operating temp range -65 to +160 degrees feh; wt 5.25 lbs

Thread Series Designator:

Unj

Furnished Items And Quantity:

1 lever

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A506h0