## NSN 4820-00-625-9816

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-625-9816

Thread Class:

3b all ends

**Thread Direction:** 

Right-hand all ends

## Flow Control Device:

Poppet

## **Disk Loading Method:**

Spring

#### **Connection Style:**

Flar (tube) all ends

#### Valve Operation Method:

Automatic

#### Connection Type:

Threaded internal tube all ends

#### **Mounting Facility:**

Threaded fastener

## Features Provided:

Pressure tight outlet side

## Thready Qty Per Inch (tpi):

1z all ends

## Maximum Operating Pressure:

150.0 pounds per square inch single response

## Thread Size:

1.312 inches all ends

#### Seat Angle:

45.0 degrees all ends

#### **Outside Diameter Tube Accommodated:**

1.000 inches all ends

#### Material:

Aluminum alloy b443.0 body or aluminum alloy 208.0 body or aluminum alloy 319.0 body or aluminum alloy 328.0 body

#### Material Specification:

Qq-a-601, t6 federal specification single material response stem

#### Surface Treatment:

Anodize

#### Style Designator:

Angle

#### **Thread Series Designator:**

Un all ends

## Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 4820-00-625-9816

Safety Relief Valve - Page 2 of 2

Demilitarization:

No

Fiig:

A046b0

