NSN 4820-00-625-9816

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-625-9816 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Connection Style:** Flar (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Mounting Facility:** Threaded fastener **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 1z all ends **Maximum Operating Pressure:** 150.0 pounds per square inch single response **Thread Size:** 1.312 inches all ends Seat Angle: 45.0 degrees all ends **Outside Diameter Tube Accommodated:** 1.000 inches all ends Material: Aluminum alloy b443.0 body or aluminum alloy 208.0 body or aluminum alloy 319.0 body or aluminum alloy 328.0 body **Material Specification:** Qq-a-601, t6 federal specification single material response stem **Surface Treatment:** Anodize **Style Designator:** Angle **Thread Series Designator:** Un all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-625-9816

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0