## NSN 4820-00-627-4407



Check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-627-4407 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 280.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 30000.0 pounds per square inch 2nd response **Thread Size:** 0.750 inches all ends Seat Angle: 37.0 degrees all ends Material: Aluminum flow control device **Material Specification:** Qq-a-225/6, alloy 2024, t4 federal specification single material response seat Media For Which Designed: Air 1st response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life: N/a

**Unit Of Measure:** 

## NSN 4820-00-627-4407

Check Valve - Page 2 of 2



_										
וו	0	m	ш	м	2	iza	31	^	n	

No

Fiig:

A530b0

Mil-std (military Standard):

Mil-a-8625 spec.