

View Online at <https://aerobasegroup.com/nsn/4820-00-627-5235>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.5 gallons per minute

Connection Style:

Flared (tube) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded external tube 1st end

Features Provided:

Valve stem lock shield and bonnet packing and pressure tight outlet side

Thready Qty Per Inch (tpi):

18 1st end

Maximum Operating Pressure:

100.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Opening Pressure Setting:

29.0 pounds per square inch

Outside Diameter Tube Accommodated:

0.375 inches 1st end

Material:

Aluminum alloy seat

Media For Which Designed:

Oil, hydraulic single response

Surface Treatment:

Anodize

Style Designator:

Straight thru

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0