

View Online at <https://aerobasegroup.com/nsn/4820-00-633-6671>

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside spring

**Bonnet Attachment Method:**

Threaded

**Disk Loading Method:**

Spring

**Valve Discharge Flow Rate:**

239.0 cubic feet per minute

**Renewable Seat Ring Type:**

Pressed-in

**Maximum Operating Temp:**

185.0 degrees fahrenheit single response

**Connection Style:**

Plain (pipe) 1st end

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded external pipe 1st end

**Features Provided:**

Pressure tight outlet side and valve stem lock shield

**Adjustable Pressure Range:**

+1.0/+6500.0 pounds per square inch

**Maximum Operating Pressure:**

6500.0 pounds per square inch single response

**Thread Size:**

0.250 inches 1st end

**Material:**

Stainless steel flow control device

**Media For Which Designed:**

Gas, inert 2nd response

**Surface Treatment:**

Anodize

**Style Designator:**

Angle

**Thread Series Designator:**

Npt 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0