NSN 4820-00-639-9086

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-639-9086

| Pip | be Size Accommodated: |
|-----|---|
| 0.3 | 375 inches 2nd end |
| Th | read Direction: |
| Riç | ght-hand 1st end |
| Flo | ow Control Device: |
| Ste | em |
| Dis | sk Loading Method: |
| Sp | ring |
| Co | onnection Style: |
| Pla | ain, optional en (pipe) 1st end |
| Va | Ive Operation Method: |
| Au | tomatic |
| Co | onnection Type: |
| Un | threaded external pipe 2nd end |
| Fe | atures Provided: |
| Va | lve stem lock shield and pressure tight outlet side |
| Th | ready Qty Per Inch (tpi): |
| 14 | 1st end |
| Th | read Size: |
| 0.5 | 500 inches 1st end |
| Op | pening Pressure Setting: |
| 15 | .0 pounds per square inch |
| Ма | aterial: |
| Ste | eel stem |
| Sty | yle Designator: |
| An | gle |
| Th | read Series Designator: |
| Np | t 1st end |
| Sh | elf Life: |
| N/a | a |
| Un | it Of Measure: |
| | |
| De | militarization: |
| No | |
| Fii | g: |
| A0 | 46b0 |