

View Online at <https://aerobasegroup.com/nsn/4820-00-639-9306>

**Bonnet Type:**

Outside screw-yoke

**Bonnet Attachment Method:**

Bolted

**Renewable Seat Ring Type:**

Threaded

**Bolt Hole Quantity:**

8 2nd end

**Valve Operation Method:**

Manual

**Flange Shape:**

Round with holes 2nd end

**Connection Type:**

Flange 1st end

**Mounting Facility:**

Threaded fastener

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

400.0 pounds per square inch single response

**Outside Diameter:**

6.625 inches 2nd end

**First Connection Face To Centerline Distance:**

10.125 inches

**Bolt Hole Diameter:**

0.563 inches 2nd end

**Second Connection Face To Centerline Distance:**

5.375 inches

**Bolt Circle Diameter:**

5.500 inches 2nd end

**Flange Face Design:**

Plain 2nd end

**Special Features:**

Integral flange 8.125 in. Od on inlet portion of valve body located 5.375 in. Center to face w/8 holes 0.813 in. Diameter equally spaced on 6.563 in. Bolt circle

**Material:**

Nickel alloy stem

**Media For Which Designed:**

Water-oil-gas single response

**Style Designator:**

Angle flanged ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0