

View Online at <https://aerobasegroup.com/nsn/4820-00-639-9306>

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

8 2nd end

Valve Operation Method:

Manual

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Mounting Facility:

Threaded fastener

Features Provided:

Bonnet packing

Maximum Operating Pressure:

400.0 pounds per square inch single response

Outside Diameter:

6.625 inches 2nd end

First Connection Face To Centerline Distance:

10.125 inches

Bolt Hole Diameter:

0.563 inches 2nd end

Second Connection Face To Centerline Distance:

5.375 inches

Bolt Circle Diameter:

5.500 inches 2nd end

Flange Face Design:

Plain 2nd end

Special Features:

Integral flange 8.125 in. Od on inlet portion of valve body located 5.375 in. Center to face w/8 holes 0.813 in. Diameter equally spaced on 6.563 in. Bolt circle

Material:

Nickel alloy stem

Media For Which Designed:

Water-oil-gas single response

Style Designator:

Angle flanged ends

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0