NSN 4820-00-640-0457

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-640-0457

Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 2nd end
Maximum Operating Temp:
650.0 degrees fahrenheit single response
Flange Shape:
Round with holes 2nd end
Connection Type:
Flange 1st end
Adjustable Pressure Range:
+10.0/+15.0 pounds per square inch
Maximum Operating Pressure:
75.0 pounds per square inch single response
Outside Diameter:
5.500 inches 1st end
Thickness:
0.625 inches 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Bolt Circle Diameter:
6.562 inches 2nd end
Flange Face Design:
Plain 2nd end
Special Features:
With sight gage
Material:
Steel uns j03008 body
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-640-0457

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0