NSN 4820-00-640-6541

Angle Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-640-6541

Pipe Size Accommodated:
0.125 inches 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Threaded
Maximum Operating Temp:
150.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Manual
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Bonnet packing
Thready Qty Per Inch (tpi):
27 1st end
27 1st end Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 300.0 pounds per square inch single response
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class Shelf Life:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class Shelf Life: N/a
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class Shelf Life: N/a
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class Shelf Life: N/a Unit Of Measure:
Maximum Operating Pressure: 300.0 pounds per square inch single response Thread Size: 0.125 inches 1st end Material: Rubber flow control device Style Designator: Angle Thread Series Designator: Npt 1st end Specification Or Standard: 2 type and b class Shelf Life: N/a Unit Of Measure: Demilitarization: