

View Online at https://aerobasegroup.com/nsn/4820-00-651-2338

| Thread Class:                                   |
|---|
| 3a 1st end                                      |
| Thread Direction:                               |
| Right-hand 1st end                              |
| Flow Control Device:                            |
| Ball  |
| Maximum Operating Temp:                         |
| 300.0 degrees fahrenheit single response        |
| Connection Style:                               |
| Flared (tube) 1st end                           |
| Valve Operation Method:                         |
| Manual  |
| Connection Type:                                |
| Unthreaded external hose 2nd end                |
| Thread Size:                                    |
| 0.500 inches 1st end                            |
| Seat Angle:                                     |
| 37.0 degrees 1st end                            |
| Face To Face Distance:                          |
| 1.460 inches                                    |
| Inside Diameter Hose Accommodated:              |
| 0.188 inches 2nd end                            |
| Special Features:                               |
| Drilled w/safety wire holes                     |
| Material:                                       |
| Aluminum  |
| Media For Which Designed:                       |
| Hydraulic fluid, petroleum base single response |
| Thread Series Designator:                       |
| Unf 1st end                                     |
| Shelf Life:                                     |
| N/a   |
| Unit Of Measure:                                |
|   |
| Demilitarization:                               |
| No  |
| Filg:   |
| A046b0  |
|   |
|   |