## NSN 4820-00-653-4478

Restrictor Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-653-4478 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Swivel nut, flareless (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube 1st end **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.750 inches all ends Seat Angle: 12.0 degrees all ends **Outside Diameter Tube Accommodated:** 0.500 inches all ends Material: Stainless steel flow control device **Material Specification:** Qq-a-225/6, alloy 2024, t4 federal specification single material response body Media For Which Designed: Fuel/oil, hydrocarbon single response **Surface Treatment:** Anodize **Special Test Features:** Non e **Style Designator:** Straight thru **Thread Series Designator:** 

Unf all ends

Shelf Life:

N/a

## NSN 4820-00-653-4478

Restrictor Check Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A530b0