NSN 4820-00-658-3144

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-658-3144 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Threaded **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 2.0 gallons per minute **Maximum Operating Temp:** 110.0 degrees fahrenheit single response **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 2nd end **Features Provided:** Valve stem lock shield and bonnet packing and pressure tight outlet side Thready Qty Per Inch (tpi): 16 1st end **Maximum Operating Pressure:** 120.0 pounds per square inch single response **Thread Size:** 0.750 inches 1st end **Opening Pressure Setting:** 150.0 pounds per square inch Material: Steel seat **Style Designator:** Angle **Thread Series Designator:** Unf 1st end Shelf Life:

N/a **Unit Of Measure:**

NSN 4820-00-658-3144

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0